

BLUE FLAME VENT-FREE HEATERS

SPECIFICATIONS

VENT-FREE, BLUE FLAME HEATER IN 10M, 20M AND 30M BTU'S, WITH TOP-OPERATED CONTROLS, PIEZO IGNITOR, 450 DEGREE NEUTRAL BONE COLORED, BAKED-ENAMEL TEXTURED-STEEL CABINETS, INSULATED FOR "COOL TOUCH" SAFETY. 10M, 20M AND 30M BTU UNITS (BFT PREFIX) SHALL FEATURE SIT EUROSIT 0.630.531 HYDROSTATIC THERMOSTAT CONTROLS – ALL ½" INLET. ALL UNITS ARE 99.9% EFFICIENT WITH "O.P." O.D.S. (OXYGEN DEPLETION SENSOR) PILOT FOR NATURAL AND L.P. GAS. UNITS INCLUDE BLACK ALLOYED SAFETY GUARD, HI-TEMPERATURE SAFETY GLASS AND CONVENIENT, REMOVABLE LOWER SERVICE PANEL. ALL UNITS FEATURE A RIGID MANIFOLD PIPE SYSTEM TO PREVENT LEAKS. A WALL MOUNTING BRACKET IS PROVIDED AS STANDARD EQUIPMENT ON ALL UNITS AND A FREESTANDING KIT IS OPTIONAL ON ALL 3 UNITS. A THERMOSTATICALLY CONTROLLED CROSSFLOW BLOWER IS PROVIDED AS OPTIONAL EQUIPMENT FOR THE 20M AND 30M BTU MODELS ONLY. ALL UNITS FEATURE A BLACK PORCELAIN ENAMEL HEARTH AND JAMB ASSEMBLY TO RADIATE HEAT, ENHANCE THE APPEARANCE, YET NOT DISCOLOR. ALL UNITS FEATURE OPTIONAL GAS INLET THAT ADJUSTS TO REAR OR BOTTOM (90°) POSITION. UNIT, BURNER AND OPTIONAL BLOWER ASSEMBLY ARE WARRANTED FOR ONE YEAR FROM DATE OF PURCHASE. ALL UNITS ARE INDIVIDUALLY PACKAGED IN WHITE CRAFT, DESCRIPTIVE, POINT-OF-PURCHASE CARTONS.