

DIRECT VENT GAS-FIRED BASEBOARD **HEATER**

SPECIFICATIONS

THE 5,000 BTU (4 FT.) AND 9,000 BTU (6 FT.) DIRECT VENT BASEBOARD HEATERS FEATURE NEUTRAL BONE HIGH TEMP BAKED ENAMEL FINISH IN A SPACE SAVING DESIGN, WITH 9 FT. POWER CORD. THE STANDARD WALL THERMOSTAT CAN OPERATE UP TO THREE (3) BASEBOARD HEATERS WIRED IN PARALLEL SERIES. THE BASEBOARD HEATERS SHALL FEATURE A HIGH EFFICIENT IN-SHOT BURNER, TRANSISTORIZED, SELF-DIAGNOSING, IGNITION MODULE, AND RELIABLE DIRECT SPARK IGNITION.

THE STANDARD VENT REQUIRES ONLY A 2-1/2" WALL OPENING. THE 24 VOLT THERMOSTATED (115 VOLT REQUIRED), DRAFT INDUCED UNIT, INCLUDES A STANDARD VENT AIR INTAKE WITH 1-1/2" I.D. SEAL, THAT ADJUSTS FROM 4-1/2" TO 16" WALL THICKNESS. OPTIONAL KITS WOULD INCLUDE: A SIDE VALVE CONCEALER KIT, BOTTOM VALVE CONCEALER KIT, VENT WEATHER KIT W/2" I.D. SEAL, AND A VENT RISER KIT. THE TUBULAR ALUMINIZED COMBUSTION CHAMBER IS WARRANTED FOR 10 YEARS – WITH NO PRO RATA. EACH UNIT INCLUDES A MOUNTING TEMPLATE TO FACILITATE INSTALLATION. CONVERSION KITS FOR NATURAL OR L.P. ARE ALSO AVAILABLE. THESE UNITS CAN REDUCE ELECTRICAL BASEBOARD CONSUMPTION BY 72%!

BOTH UNITS MAY BE SHIPPED VIA U.P.S.

02/2004