

DIRECT VENT WALL FURNACE

SPECIFICATIONS

15,000 BTU, 25,000 BTU, OR 33,000 BTU INPUT DIRECT VENT WALL FURNACE IN NEUTRAL BONE COLOR, WITH A 450 DEGREE HIGH-TEMP BAKED ENAMEL FINISH. UNITS WILL FEATURE DEXEN CONTROLS WITH LOW-BTU, 100% SAFETY PILOT, AND PIEZO MANUAL SPARK IGNITOR. A WALL MOUNTED THERMOSTAT IS STANDARD (WITH 20 FEET OF WIRE AND INSULATED STAPLES), OR AN OPTIONAL BUILT-IN BULB STAT KIT (BBSK) IS AVAILABLE. UNITS WILL FEATURE A 430 STAINLESS STEEL BURNER. VENT CAP FOR UP TO 9" THICK WALL (5" MINIMUM) WILL BE STANDARD ON ALL UNITS & CAP SHALL BE BIRD AND PEE PROOF. OPTIONAL EXTENSION KITS SHALL BE AVAILABLE FOR WALL THICKNESSES GREATER THAN 9" UP TO 15" THICK (ALL MODELS), AND 24" THICK ON 15M AND 25M BTU UNITS. UNITS SHALL NOT REQUIRE A VINYL SIDING KIT. COMBUSTION CHAMBER SHALL BE CONSTRUCTED OF CONTINUOUS SEAM WELDED ALUMINIZED STEEL AND WARRANTED FOR TEN (10) YEARS WITH NO PRO RATA. AN OPTIONAL, THERMOSTATICALLY CONTROLLED BLOWER WITH 81 CFM'S IS AVAILABLE FOR ALL THREE UNITS. EACH UNIT SHALL INCLUDE A MOUNTING TEMPLATE TO FACILITATE INSTALLATION. CONVERSION KITS FOR NATURAL OR L.P. GAS ARE AVAILABLE.

12/2004