

GAS FIRED FLOOR FURNACES

SPECIFICATIONS

30,000 BTU (14-1/4"X32-1/4"), 50,000 BTU (22-1/2"X32-1/2"), 62,500 BTU (24-1/2"X 38-1/2"), OR 75,000 BTU (26-1/2" X 42-1/2") FLOOR FURNACES. HONEYWELL MILLIVOLT CONTROLS WITH 750 MILLIVOLT POWERPILE, LOW-BTU 100% SAFETY PILOT, FACTORY INSTALLED PRESSURE REGULATOR. WALL THERMOSTAT, 20 FEET OF WIRE AND INSULATED STAPLES WILL BE PROVIDED AS STANDARD EQUIPMENT. A DRAFT DIVERTER WILL BE PROVIDED WITH EACH UNIT. THE 30,000 BTU UNIT (NARROW WIDTH) SHALL FIT BETWEEN A STANDARD 16" CENTER FLOOR JOIST. ALL UNITS WILL FEATURE ALUMINIZED STEEL BURNERS AND A COLD ROLLED CONTINUOUS-SEAM WELDED STEEL COMBUSTION CHAMBER, WARRANTED FOR TEN (10) YEARS – NO PRO RATA. EACH UNIT SHALL FEATURE REDUNDANT SAFETY HIGH LIMIT CONTROL TO CYCLE UNIT OFF IN THE EVENT OF GRILL BLOCKAGE. EACH UNIT WILL INCLUDE AN OPERATING KEY, LIGHTER ROD AND PYREX VISION CAP ASSEMBLY.

09/1998