

# **INFRARED VENT-FREE HEATERS**

## **SPECIFICATIONS**

VENT-FREE, INFRARED HEATER IN 5/5.5M, 10M, 20M AND 30M BTU'S, WITH TOP-OPERATED CONTROLS, PIEZO IGNITOR, 450 DEGREE NEUTRAL BONE COLORED, BAKED-ENAMEL TEXTURED-STEEL CABINetry, INSULATED FOR "COOL TOUCH" SAFETY. 5/5.5M, 10M AND 20M BTU UNITS (VFM PREFIX) SHALL FEATURE MANUAL COPRECI CPMM-21400/117, WHILE 10M, 20M AND 30M BTU UNITS (VFT PREFIX) INCLUDE SIT EUROSIT 0.630.531 HYDROSTATIC THERMOSTAT CONTROLS – ALL ½" INLET. ALL UNITS ARE 99.9% EFFICIENT WITH "O.P." O.D.S. (OXYGEN DEPLETION SENSOR) PILOT FOR NATURAL AND L.P. GAS. UNITS INCLUDE CHROME ALLOYED SAFETY GUARD AND REMOVABLE LOWER SERVICE PANEL. THE 10M, 20M AND 30M BTU THERMOSTATIC UNITS FEATURE A RIGID MANIFOLD PIPE SYSTEM TO PREVENT LEAKS. A WALL MOUNTING BRACKET IS PROVIDED AS STANDARD EQUIPMENT ON ALL UNITS AND A FREESTANDING KIT IS OPTIONAL ON 10M, 20M, AND 30M BTU UNITS. A THERMOSTATICALLY CONTROLLED CROSSFLOW BLOWER IS PROVIDED AS OPTIONAL EQUIPMENT FOR THE 20M AND 30M BTU MODELS ONLY. ALL UNITS FEATURE AN EARTHTONE, PORCELAIN ENAMEL HEARTH AND JAMB ASSEMBLY TO RADIATE HEAT, ENHANCE THE UNIT APPEARANCE, YET NOT DISCOLOR. ALL UNITS FEATURE OPTIONAL GAS INLET THAT ADJUSTS TO REAR OR BOTTOM (90°) POSITION. UNIT, BURNER AND OPTIONAL BLOWER ASSEMBLY ARE WARRANTED FOR ONE YEAR FROM DATE OF PURCHASE. ALL UNITS ARE INDIVIDUALLY PACKAGED IN WHITE CRAFT, DESCRIPTIVE, POINT-OF-PURCHASE CARTONS.