

CONVENTIONAL VENT **COUNTERFLOW WALL FURNACE** **WITH STANDING PILOT**

SPECIFICATIONS

35,000 BTU (14-5/16" W X 10-1/4" D X 78-5/8" H), 50,000 BTU (14-5/16" W X 10-1/4" D X 81-5/16" H) OR 65,000 BTU (14-5/16" W X 10-1/4" D X 87-5/16" H) COUNTERFLOW WALL FURNACE WITH NEUTRAL BONE COLORED HIGH-TEMP BAKED ENAMEL CABINET OF TEXTURED STEEL. UNITS SHALL FEATURE 24 VOLT HONEYWELL CONTROLS WITH A LOW-BTU ENERGY EFFICIENT 100% SAFETY PILOT AND FACTORY INSTALLED PRESSURE REGULATOR. UNIT SHALL FEATURE A RESETTABLE BLOCKED FLUE SWITCH IN THE DRAFTHOOD. FURNACE WILL HAVE WALL THERMOSTAT, TWENTY (20) FEET OF WIRE AND INSULATED STAPLES. THEY SHALL INCORPORATE NO. 430 STAINLESS STEEL ALLOY BURNER, AND A CONTINUOUS SEAM WELDED ALUMINIZED COMBUSTION CHAMBER, WARRANTED FOR TEN (10) YEARS – NO PRO RATA. THEY WILL ALSO FEATURE 320 CFM (35M BTU), 340 CFM (50M BTU) OR 440 CFM (65M BTU) THERMOSTATICALLY CONTROLLED FAN, MACMILLAN MOTOR IS .0409 H.P. @ 1,050 RPM. ALL UNITS SHALL FEATURE A MANUAL RESET AUXILIARY LIMIT SWITCH ACCESSED THROUGH CONTROL DOOR. UNITS WILL ACCOMMODATE OPTIONAL SIDE AND REAR OUTLET KITS FOR HEAT DISPERSAL TO OTHER ROOMS AS NEEDED. UNITS ALSO FEATURE A TRIM KIT TO FINISH RECESS APPLICATIONS. UNITS SHALL FIT BETWEEN STANDARD 16" STUD SPACE AND BE RECESSIBLE UP TO 9-1/4". CONVERSION KITS FOR NATURAL OR L.P. GAS ARE AVAILABLE.

08/2005

CONVENTIONAL VENT
COUNTERFLOW WALL FURNACE
WITH INTERMITTENT IGNITION
DEVICE

SPECIFICATIONS

35,000 BTU (14-5/16" W X 10-1/4" D X 78-5/8" H) OR 55,000 BTU (14-5/16" W X 10-1/4" D X 87-5/16" H) INPUT CONVENTIONAL VENT (4" OVAL BW) COUNTERFLOW WALL FURNACE WITH NEUTRAL BONE COLORED, HIGH-TEMP BAKED ENAMEL CABINET OF TEXTURED STEEL. UNIT SHALL FEATURE 24 VOLT HONEYWELL CONTROLS WITH A SPARK TYPE INTERMITTENT IGNITION DEVICE. UNITS SHALL FEATURE A RESETTABLE, BLOCKED FLUE SWITCH IN THE DRAFTHOOD. FURNACE WILL HAVE WALL THERMOSTAT, TWENTY (20) FEET OF WIRE AND INSULATED STAPLES. THEY SHALL INCORPORATE NO. 430 STAINLESS STEEL ALLOY BURNER, AND A CONTINUOUS SEAM WELDED ALUMINIZED COMBUSTION CHAMBER, WARRANTED FOR TEN (10) YEARS – NO PRO RATA. THEY WILL ALSO FEATURE 320 CFM (35M BTU) OR 440 CFM (55M BTU) THERMOSTATICALLY CONTROLLED FAN. MACMILLAN MOTOR IS .0409 H.P. @ 1,050 RPM. ALL UNITS SHALL FEATURE A MANUAL RESET HIGH LIMIT SWITCH ACCESSED THROUGH CONTROL DOOR. UNITS WILL ACCOMMODATE OPTIONAL SIDE AND REAR OUTLET KITS FOR HEAT DISPERAL TO OTHER ROOMS AS NEEDED. UNITS ALSO FEATURE A TRIM KIT TO FINISH RECESS APPLICATIONS. UNITS SHALL FIT BETWEEN STANDARD 16" STUD SPACE AND BE RECESSIBLE UP TO 9-1/4". CONVERSION KITS FOR NATURAL OR L.P. GAS ARE AVAILABLE.

08/2005